



# 東芝照明器具配光データシート

名称	蛍光灯器具
形名	FR-44003PEX K-GL

保守率	良	0.74
	中	0.70
	否	0.61



光源	名称	蛍光ランプ
	形名	FL40SS・EX-N /37-H
	光束	3560 lm × 1

効率	F	4%
	F	85%
	F	89%
	器具光束	3177 lm

最大取付間隔	
A-A	1.4 H
B-B	1.3 H

備考	
----	--

前面	下面開放
反射面	塗装 (白)

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	219	219	219
10°	217	216	217
20°	212	205	208
30°	206	187	195
40°	197	164	180
50°	183	135	161
60°	166	102	138
70°	142	65	112
80°	126	25	86
90°	90	0	58
100°	37	0	11
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井		80				70				50				30		20	0		
	壁	床	70	50	30	10	70	50	30	10	70	50	30	10	50	30	30	10		
室指数	照明率 (×0.01)																			
0.60	51	47	37	35	29	28	49	45	36	35	29	28	35	33	28	27	27	26	22	20
0.80	61	55	47	44	38	37	59	54	46	43	38	36	44	42	36	35	35	34	30	27
1.00	67	60	54	50	44	42	65	59	52	49	44	42	49	47	42	40	40	39	34	32
1.25	74	66	61	56	52	48	71	64	59	55	50	48	56	52	48	46	46	45	40	38
1.50	79	69	66	60	57	53	75	67	64	59	56	52	60	56	53	50	51	49	44	42
2.00	86	75	75	67	66	60	83	73	73	66	64	60	68	63	61	58	58	56	51	49
2.50	91	78	81	71	72	65	87	76	78	70	70	64	72	67	66	62	63	60	56	53
3.00	94	81	85	74	77	69	90	79	82	73	75	68	76	70	71	66	67	64	60	57
4.00	99	84	91	79	84	74	94	82	88	77	82	73	81	74	76	71	72	68	65	62
5.00	102	86	95	81	89	77	97	84	91	80	86	76	84	77	80	74	75	71	68	65
10.00	108	90	104	88	100	85	103	88	100	86	96	84	92	83	89	81	83	78	76	73

