




UNIT : cd/1000 lm



(単位 : %)

反射率 (%) REFLECTANCE	天井	80			70			50			30			0
	壁	70	50	30	70	50	30	70	50	30	70	50	30	0
室指数 (Kr) ROOM INDEXES	床	10			10			10			10			0
	0.60	47	35	27	44	34	27	40	31	25	37	29	23	16
Kr = $\frac{XY}{H(X+Y)}$	0.80	54	43	35	52	41	34	47	38	32	43	35	30	22
	1.00	60	50	42	58	48	40	52	44	38	48	41	35	27
BZ 6	1.25	65	55	47	62	53	46	57	49	43	52	45	40	31
	1.50	70	60	53	66	58	51	61	53	48	55	49	45	35
最大取付間隔 MAX SPACING	2.00	75	67	60	72	64	58	66	59	54	60	55	51	41
	2.50	78	71	65	75	69	63	69	64	59	63	59	55	46
A-A' 1.45 B-B' 1.20 H	3.00	81	74	69	78	72	67	71	66	62	65	62	58	49
	4.00	84	79	74	81	76	72	75	71	67	69	65	63	53
備考 REMARK	5.00	86	82	78	83	79	75	77	73	70	71	68	66	56
	7.00	89	85	82	85	82	79	79	77	74	73	71	69	60
	10.00	91	88	85	87	85	83	81	79	77	75	74	72	64

器具形式 LUMINAIRE TYPE	FHV16201EKX9	器具効率 LUMINAIRE EFFICIENCY	上方 UPPER	17.9 %	配光特性 LUMINOUS INTENSITY DISTRIBUTION
光源形式 LAMP TYPE	FHF16EX-N-H		下方 LOWER	74.0 %	
光源光束 LAMP FLUX	2100 x 2 lm		総計 TOTAL	91.9 %	器具名称 LUMINAIRE DESIGNATION
備考 REMARK				図番 SHEET NO.	DY001992

