

# 屋内照明器具特性

品番 (品名)	F S A 4 2 0 0 1 F														
光源	FHF32EX-N-H(3520) ×2      3520.0 l m														
管理番号	K0082706 (* ) DB 1														
BZ分類	BZ6														

器具効率	92 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	18 %	室指数	照明率 ( X0.01 )																ZCM		
下方光束	74 %																				
保守率	良 0.73 中 0.69 否 0.61	0.6	46	34	27	21	44	33	26	21	40	30	24	20	36	28	23	19	16		
		0.8	54	43	35	29	52	41	34	29	47	38	32	27	43	35	30	26	22		
		1.0	60	49	41	35	57	47	40	34	52	44	37	32	47	40	35	31	26		
		1.25	65	55	48	42	62	53	46	40	57	49	43	38	51	45	40	36	31		
下方投影面積	c m <sup>2</sup>	1.5	69	60	52	46	66	57	51	45	60	53	47	43	55	49	44	40	35		
		2.0	74	66	60	54	71	64	58	52	65	59	54	49	59	54	50	46	41		
取付高さ	器具間隔最大限		2.5	78	71	65	59	75	68	62	58	68	63	58	54	63	58	54	51	45	
	横方向 (A)	縦方向 (B)	3.0	80	74	68	64	77	71	66	62	71	66	62	58	65	61	57	54	48	
1.5m	2.3 m	2.17 m	4.0	84	78	74	69	80	76	71	67	74	70	66	63	68	65	62	59	53	
2	3.03	2.73	5.0	86	81	77	73	82	78	75	71	76	73	70	67	70	67	65	63	56	
2.5	3.76	3.31	7.0	88	85	81	78	85	82	79	76	79	76	74	71	73	71	69	67	59	
3	4.48	3.91	10.0	90	88	85	83	87	85	82	80	81	79	77	75	75	73	72	70	63	

