

屋内照明器具特性

品番 (品名)	FHA82268F														
光源	FHF86EN/RX x2 9200.0 1m														
管理番号	K0083395 (4) DB1														
BZ分類	BZ6/0.9/BZ5														

器具効率	88 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	2 %																			
下方光束	86 %																			
室指数	照明率 (X0.01) ZCM																			
保守率	良 中 否	0.73	0.6	47	36	29	23	46	35	28	23	43	34	28	23	41	33	27	23	21
		0.69	0.8	56	45	37	32	54	44	37	32	51	43	36	32	49	41	36	31	29
			1.0	61	51	44	38	60	50	43	38	57	49	42	38	54	47	42	37	35
		0.61	1.25	67	57	50	45	65	56	50	44	62	54	49	44	59	53	48	43	41
下方投影面積	c m ²	1.5	71	62	55	50	69	61	54	49	66	59	53	49	63	57	52	48	45	
		2.0	76	68	62	57	74	67	62	57	71	65	60	56	68	63	59	55	52	
等価発光面積	c m ²	2.5	79	73	67	63	77	71	66	62	74	69	65	61	71	67	63	60	57	
		3.0	81	76	71	67	80	75	70	66	77	72	68	65	74	70	67	64	61	
取付高さ	器具間隔最大限		4.0	84	80	76	72	83	79	75	71	80	76	73	70	77	74	71	69	66
	横方向 (A)	縦方向 (B)																		
1.5m	2.29 m	2.84 m	5.0	86	82	79	76	85	81	78	75	82	79	76	73	79	76	74	72	69
2	2.98	3.28	7.0	89	86	83	80	87	84	82	80	84	82	80	78	81	80	78	76	73
2.5	3.68	3.78	10.0	90	88	86	84	89	87	85	83	86	84	83	81	83	82	81	79	76
3	4.37	4.33																		

