



東芝照明器具配光データシート

名称	蛍光灯器具
形名	FHR-42713N-PD9

保守率	良	0.73
	中	0.69
	否	0.61



光源	名称	メロウライン
	形名	FHF32EX-N-H
	光束	4950 lm x 2

効率	F	0%
	F	72%
	F	72%
	器具光束	7116 lm

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備考	
----	--

前面	
反射面	塗装 (白)

光度 (cd/1000lm)			
θ	A-A	B-B	C-C
0°	271	270	271
10°	262	269	270
20°	255	256	260
30°	237	235	242
40°	192	206	211
50°	124	171	160
60°	61	130	94
70°	33	83	40
80°	13	31	15
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井		80				70				50				30		20		0	
	壁	床	70	50	30	10	70	50	30	10	70	50	30	10	50	30	30	10	10	0
室指数	照明率 (x0.01)																			
0.60	47	43	37	35	31	30	45	42	36	34	30	30	35	34	30	29	29	29	26	25
0.80	56	51	46	43	40	38	54	50	45	43	39	38	44	42	38	37	38	37	34	32
1.00	61	55	51	48	45	43	59	54	50	47	44	42	49	46	43	42	42	41	38	37
1.25	66	59	57	53	51	48	64	58	56	52	50	47	54	51	49	47	48	46	43	42
1.50	70	62	62	56	55	51	68	61	60	55	54	51	58	54	53	50	51	49	47	45
2.00	76	66	69	61	63	57	73	65	67	60	62	57	64	59	59	56	57	55	52	51
2.50	79	68	73	64	67	61	76	67	71	63	66	60	67	62	63	59	61	58	56	54
3.00	81	70	76	66	71	63	79	69	74	65	69	63	70	64	66	62	63	61	58	57
4.00	84	72	80	69	76	67	81	71	77	68	74	66	73	67	70	65	67	64	62	60
5.00	86	73	82	71	79	69	83	72	80	70	77	68	75	68	73	67	69	65	64	62
10.00	90	75	88	74	86	73	87	74	85	73	83	72	79	72	78	71	73	69	68	67

