




東芝照明器具配光データシート



名称	蛍光灯器具
形名	FHR-42861N-PM9

光源	名称	蛍光ランプ
	形名	FHF32EX-N-H
	光束	3520 lm × 2

前面	バッフル (白)
反射面	塗装 (白)

保守率	良	0.69
	中	0.65
	否	0.61

効率	F 	0%
	F 	75%
	F 	75%
	器具光束	5267 lm



最大取付間隔	
A-A	1.3 H
B-B	1.2 H

備考	
----	--

θ \ φ	光度 (cd/1000lm)		
	A-A	B-B	C-C
0°	295	295	295
10°	295	286	290
20°	288	265	277
30°	264	235	251
40°	228	199	212
50°	179	156	165
60°	82	108	109
70°	30	57	40
80°	11	18	15
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井		80				70				50				30		20	0		
	壁	床	70	50	30	10	70	50	30	10	70	50	30	10	70	50	10	0		
室指数	照明率 (×0.01)																			
0.60	49	45	39	37	33	31	48	44	38	36	32	31	37	36	32	31	31	31	27	26
0.80	59	53	48	45	42	40	57	52	48	45	42	40	46	44	41	39	40	39	36	35
1.00	64	57	54	50	48	45	62	56	53	50	47	45	51	49	46	44	45	44	40	39
1.25	70	62	60	55	54	51	68	61	59	55	53	50	57	53	52	49	50	49	46	44
1.50	73	65	65	59	58	54	71	63	63	58	57	54	61	57	56	53	54	52	49	48
2.00	79	69	72	64	66	60	77	68	70	64	65	60	67	62	62	59	60	58	55	54
2.50	83	71	76	67	71	64	80	70	74	66	69	63	70	65	66	62	64	61	59	57
3.00	85	73	79	69	74	66	82	72	77	69	73	66	73	67	69	65	67	64	61	60
4.00	88	75	84	72	80	70	85	74	81	71	77	69	76	70	74	68	70	67	65	63
5.00	90	76	86	74	83	72	87	75	83	73	80	71	78	71	76	70	72	69	67	65
10.00	94	78	92	77	90	76	90	78	89	76	87	75	83	75	81	74	77	73	71	70

