



東芝照明器具配光データシート

名称	蛍光灯器具
形名	FHR-43478NK-PM9

保守率	良	0.73
	中	0.69
	否	0.61



光源	名称	蛍光ランプ
	形名	FHF32EX-N-H
	光束	3520 lm x 3

効率	F	0%
	F	80%
	F	80%
	器具光束	8483 lm

最大取付間隔	
A-A	1.5 H
B-B	1.3 H

備考

前面	下面開放
反射面	塗装 (白)

θ	φ	光度 (cd/1000lm)		
		A-A	B-B	C-C
0°		224	224	224
10°		226	214	224
20°		227	206	220
30°		225	191	210
40°		217	171	199
50°		195	142	180
60°		159	108	148
70°		104	68	106
80°		41	26	45
90°		0	0	0
100°		0	0	0
110°		0	0	0
120°		0	0	0
130°		0	0	0
140°		0	0	0
150°		0	0	0
160°		0	0	0
170°		0	0	0
180°		0	0	0

反射率 (%)	天井		80				70				50				30		20		0	
	壁	床	70	50	30	70	50	30	50	30	50	30	30	10	10	10	0			
室指数	照明率 (x0.01)																			
0.60	48	44	36	34	29	28	46	43	35	33	28	27	34	33	28	27	27	27	23	21
0.80	57	52	45	43	38	36	56	51	45	42	37	36	43	41	36	35	36	35	31	29
1.00	63	57	52	48	44	41	61	56	51	47	43	41	48	46	42	40	41	40	36	34
1.25	70	62	59	54	51	48	68	61	57	53	50	47	55	52	48	46	47	46	42	40
1.50	74	65	64	58	56	52	72	64	62	57	55	51	59	55	53	50	51	50	46	44
2.00	81	71	72	64	65	59	78	69	70	64	64	59	67	62	61	58	59	57	53	51
2.50	85	74	77	68	71	64	82	72	75	67	69	63	71	66	66	62	63	61	57	56
3.00	88	76	81	71	75	67	85	75	79	70	73	66	74	68	70	65	67	64	61	59
4.00	92	79	87	75	81	72	89	77	84	74	79	71	79	72	75	69	72	68	66	64
5.00	95	80	90	77	85	74	91	79	87	76	83	74	82	74	78	72	74	71	68	67
10.00	100	84	97	82	95	80	96	82	94	81	92	80	88	79	86	78	81	76	75	73

