



# 東芝照明器具配光データシート

名称	蛍光灯器具
形名	FR-24751N

保守率	良	0.70
	中	0.66
	否	0.61



光源	名称	蛍光ランプ
	形名	FL20SS・EX-N /18-H
	光束	1470 lm × 4

効率	F	0%
	F	77%
	F	77%
	器具光束	4518 lm

最大取付間隔	
A-A	1.3 H
B-B	1.2 H

備考	
----	--

前面	バツフル (白)
反射面	塗装 (白)

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	307	307	307
10°	307	297	303
20°	297	273	287
30°	271	241	258
40°	237	202	216
50°	187	157	169
60°	91	106	112
70°	32	52	43
80°	10	17	15
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井			70			50			30			20			0				
	壁	70	50	30	70	50	30	50	30	30	10	30	10	30	10	30	10	0		
床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10		
室指数	照明率 (×0.01)																			
0.60	50	46	40	38	34	32	49	45	39	37	33	32	38	37	33	32	32	28	27	
0.80	60	55	50	47	43	41	59	54	49	46	43	41	47	45	42	41	41	40	37	36
1.00	66	59	56	52	49	46	64	58	55	51	48	46	53	50	47	46	46	45	42	40
1.25	72	64	62	57	55	52	69	62	61	56	55	52	58	55	53	51	52	50	47	46
1.50	75	66	67	60	60	56	73	65	65	60	59	55	62	58	57	55	56	54	51	49
2.00	82	71	74	66	68	62	79	70	72	65	67	62	69	64	64	61	62	60	57	55
2.50	85	73	78	69	73	66	82	72	76	68	71	65	72	67	68	64	66	63	60	59
3.00	87	75	82	71	77	68	84	74	79	71	75	68	75	69	71	67	68	65	63	62
4.00	91	77	86	74	82	72	87	76	83	73	80	71	79	72	76	70	72	69	67	65
5.00	93	78	89	76	85	74	89	77	86	75	83	73	81	73	78	72	74	71	69	67
10.00	96	81	94	79	92	78	93	80	91	79	89	78	85	77	84	76	79	75	73	72

