

東芝照明器具配光データシート



名 称	蛍光灯器具
形 名	FHT-41386N-PH9

光源	名 称	蛍光ランプ
	形 名	FHF32EX-N-H
	光 束	4950 lm × 1

前 面	
反射面	塗装（白）

保守率	良	0.73
	中	0.69
	否	0.61

効 率	F 	28%
	F 	64%
	F 	92%
	器具光束	4548 lm



最大取付間隔	
A-A	1.6 H
B-B	1.2 H

備 考	
-----	--

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	133	133	133
10°	136	131	134
20°	139	123	132
30°	144	112	129
40°	147	96	126
50°	147	76	119
60°	142	54	110
70°	130	30	96
80°	119	10	82
90°	113	0	74
100°	113	0	76
110°	114	0	81
120°	117	0	74
130°	103	0	31
140°	38	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井	80						70						50						30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		照 明 率 (×0.01)																					
0.60		48	44	35	33	27	26	45	42	33	31	26	25	29	28	23	22	21	20	16	13		
0.80		58	53	44	41	35	34	54	49	42	39	33	32	37	35	30	29	27	26	21	18		
1.00		64	58	51	47	41	39	60	54	48	44	39	37	42	40	35	34	31	30	25	21		
1.25		71	63	58	53	48	45	66	59	54	50	46	43	48	45	41	39	36	35	30	25		
1.50		75	66	63	57	53	50	70	63	59	54	50	47	52	48	45	43	40	38	33	28		
2.00		83	72	72	64	63	57	77	68	67	61	59	54	59	54	52	49	46	44	39	33		
2.50		87	75	77	68	69	62	81	71	72	65	65	59	63	58	57	53	50	48	42	37		
3.00		91	78	81	71	74	66	84	74	76	68	69	63	66	61	61	57	53	51	45	40		
4.00		95	81	87	76	81	71	88	77	82	72	75	67	71	65	66	61	58	55	50	43		
5.00		98	83	91	78	85	74	91	79	85	75	80	71	74	67	70	64	61	58	52	46		
10.00		105	87	100	85	96	82	97	83	93	81	90	78	81	73	78	71	68	64	59	53		

