

屋内照明器具特性	
品番 (品名)	F A 2 1 0 3 8 F
光源	FL20S.W ×1          1 2 3 0 . 0 1 m
管理番号	K0084049 ( 7 ) DR 1
B Z 分類	B Z 7

器具効率	93 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	27 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	66 %	室指数	照明率 ( X0.01)																Z C M	
保守率	良	0.74	0.6	4.4	3.2	2.5	1.9	4.2	3.1	2.4	1.9	3.7	2.8	2.1	1.7	3.2	2.5	1.9	1.6	1.2
	中	0.7	0.8	5.2	4.1	3.3	2.7	4.9	3.9	3.1	2.6	4.4	3.5	2.8	2.4	3.8	3.1	2.6	2.2	1.7
	否	0.61	1.0	5.8	4.7	3.9	3.3	5.5	4.5	3.7	3.1	4.8	4.0	3.4	2.9	4.2	3.6	3.0	2.6	2.1
			1.25	6.3	5.3	4.5	3.9	6.0	5.0	4.3	3.7	5.3	4.5	3.9	3.4	4.7	4.0	3.5	3.1	2.5
下方投影面積			1.5	6.7	5.8	5.0	4.4	6.3	5.5	4.8	4.2	5.6	4.9	4.3	3.9	5.0	4.4	3.9	3.5	2.9
			2.0	7.3	6.4	5.7	5.1	6.9	6.1	5.5	4.9	6.1	5.5	5.0	4.5	5.4	4.9	4.5	4.1	3.4
取付高さ	器具間隔最大限		2.5	7.6	6.9	6.2	5.7	7.2	6.5	5.9	5.4	6.4	5.9	5.4	5.0	5.7	5.3	4.9	4.5	3.8
	横方向 (A)	縦方向 (B)	3.0	7.9	7.2	6.6	6.1	7.4	6.8	6.3	5.9	6.7	6.2	5.7	5.4	5.9	5.5	5.2	4.9	4.1
1.5m	2.55 m	1.92 m	4.0	8.2	7.6	7.1	6.7	7.8	7.3	6.8	6.4	7.0	6.6	6.2	5.9	6.3	5.9	5.6	5.4	4.5
2	3.38	2.52	5.0	8.4	7.9	7.5	7.1	8.0	7.6	7.2	6.8	7.2	6.9	6.5	6.2	6.5	6.2	5.9	5.7	4.8
2.5	4.23	3.13	7.0	8.7	8.3	7.9	7.6	8.2	7.9	7.6	7.3	7.5	7.2	6.9	6.7	6.7	6.5	6.3	6.1	5.2
3	4.99	3.68	10.0	8.9	8.6	8.3	8.1	8.5	8.2	8.0	7.7	7.7	7.5	7.3	7.1	6.9	6.8	6.6	6.4	5.5

