

屋内照明器具特性

品番 (品名)	F S A 2 1 0 0 0 F									
光源	FHF16EX-N-H(2100) ×1 2100.0 l m									
管理番号	K0094113 (2) DB 1									
BZ分類	BZ7/1.1/BZ6/3.5/BZ7/4.5/BZ6									

器具効率	94 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		25 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		69 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.73	0.6	45	33	26	20	43	32	25	20	38	29	23	18	34	26	21	17	13	
	中	0.69	0.8	54	42	34	28	51	40	33	27	45	36	30	25	40	33	27	23	19	
	否	0.61	1.0	60	48	40	34	56	46	38	33	50	41	35	30	44	37	32	28	23	
			1.25	65	54	47	40	61	52	45	39	55	47	41	36	48	42	37	33	27	
下方投影面積	c m ²		1.5	69	59	51	45	65	56	49	44	58	51	45	40	51	46	41	37	30	
	等価発光面積		c m ²	2.0	74	66	59	53	70	63	56	51	63	57	51	47	56	51	47	43	36
取付高さ	器具間隔最大限		2.5	78	70	64	59	74	67	61	56	66	61	56	52	59	55	51	47	40	
	横方向 (A)	縦方向 (B)	3.0	80	74	68	63	76	70	65	60	69	64	59	55	61	57	54	51	43	
1.5m	2.43 m	1.92 m	4.0	84	78	73	69	80	75	70	66	72	68	64	61	65	61	58	56	47	
2	3.22	2.53	5.0	86	81	77	73	82	77	74	70	74	70	67	64	67	64	61	59	50	
2.5	4.03	3.14	7.0	88	85	81	78	84	81	78	75	77	74	71	69	69	67	65	63	54	
3	4.85	3.76	10.0	90	88	85	82	86	84	81	79	79	77	75	73	71	70	68	67	57	

