

屋内照明器具特性

品番 (品名)	F S A 2 2 0 0 0 J				
光源	FHF16EX-N-H(2100) ×2 2100.0 l m				
管理番号	K0086548(4)DR1				
BZ分類	BZ6				

器具効率	92%	天井	80%				70%				50%				30%				0%		
	上方光束		18%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		74%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM	
保守率	良 中 否	0.73	0.6	4.6	3.4	2.7	2.1	4.4	3.3	2.6	2.1	4.0	3.0	2.4	2.0	3.6	2.8	2.3	1.9	1.6	
		0.69	0.8	5.4	4.3	3.5	2.9	5.2	4.1	3.4	2.9	4.7	3.8	3.2	2.7	4.3	3.5	3.0	2.6	2.2	
		0.61	1.0	6.0	4.9	4.1	3.5	5.7	4.7	4.0	3.4	5.2	4.4	3.7	3.3	4.7	4.0	3.5	3.1	2.7	
		下方投影面積	c m ²		1.25	6.5	5.5	4.8	4.2	6.2	5.3	4.6	4.0	5.7	4.9	4.3	3.8	5.2	4.5	4.0	3.6
取付高さ	器具間隔最大限		2.5	7.8	7.1	6.5	5.9	7.5	6.8	6.3	5.8	6.8	6.3	5.8	5.4	6.3	5.8	5.4	5.1	4.5	
	横方向 (A)	縦方向 (B)																			
1.5m	2.23m	1.93m	4.0	8.4	7.8	7.4	7.0	8.0	7.6	7.1	6.7	7.4	7.0	6.7	6.3	6.8	6.5	6.2	5.9	5.3	
2	2.96	2.53	5.0	8.6	8.1	7.7	7.3	8.2	7.8	7.5	7.1	7.6	7.3	7.0	6.7	7.0	6.8	6.5	6.3	5.6	
2.5	3.69	3.14	7.0	8.8	8.5	8.1	7.8	8.5	8.2	7.9	7.6	7.9	7.6	7.4	7.1	7.3	7.1	6.9	6.7	6.0	
3	4.45	3.75	10.0	9.0	8.8	8.5	8.3	8.7	8.5	8.2	8.0	8.1	7.9	7.7	7.5	7.5	7.3	7.2	7.0	6.3	

