

屋内照明器具特性

品番 (品名)	F S A 4 1 0 3 8 F				
光源	FHF32EX-N-H(3520) ×1 3520.0 l m				
管理番号	K0082726 (*) DB 1				
BZ分類	BZ7/1.1/BZ6/3.5/BZ7/4.5/BZ6				

器具効率	94 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		26 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		68 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.73	0.6	45	33	25	20	42	31	24	19	38	28	22	18	33	25	20	16	13	
	中	0.69	0.8	53	42	34	28	50	40	32	27	45	36	29	25	39	32	27	23	18	
	否	0.61	1.0	59	48	40	34	56	46	38	32	49	41	35	30	44	37	32	27	22	
			1.25	64	54	46	40	61	51	44	38	54	46	40	35	48	41	36	32	27	
下方投影面積	c m ²		1.5	68	59	51	45	65	56	49	43	57	50	44	40	51	45	40	36	30	
等価発光面積	c m ²		2.0	74	65	58	53	70	62	56	51	62	56	51	46	55	50	46	42	35	
取付高さ	器具間隔最大限		2.5	77	70	63	58	73	66	61	56	66	60	55	51	58	54	50	47	39	
	横方向 (A)	縦方向 (B)																			
1.5m	2.59 m	2.13 m	3.0	80	73	67	62	76	70	64	60	68	63	59	55	61	57	53	50	42	
2	3.41	2.69	4.0	83	78	73	68	79	74	70	65	71	67	63	60	64	61	58	55	46	
2.5	4.23	3.27	5.0	85	80	76	72	81	77	73	69	73	70	67	64	66	63	61	58	49	
3	5.04	3.86	7.0	88	84	81	77	84	80	77	74	76	73	71	68	68	66	64	62	53	
			10.0	90	87	84	82	86	83	81	78	78	76	74	72	71	69	67	66	56	

