

屋内照明器具特性

品番 (品名)	FA21021Z														
光源	FL20S.W ×1 1230.0 lm														
管理番号	K0001357 (*) DR 1														
BZ分類	BZ7														

器具効率	94 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	29 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	65 %	室指数	照明率 (X0.01) ZCM																	
保守率	良 中 否 0.74 0.7 0.61	0.6	45	33	25	20	42	31	24	19	37	28	21	17	32	24	19	15	12	
		0.8	53	41	33	27	49	39	31	26	43	35	28	24	38	31	25	21	17	
		1.0	58	47	39	33	55	45	37	31	48	40	34	29	42	35	30	26	20	
		1.25	64	53	45	39	60	50	43	37	53	45	39	34	46	40	35	31	25	
下方投影面積	c m ²	1.5	68	58	50	44	64	55	48	42	56	49	43	38	49	43	39	35	28	
		2.0	73	64	57	52	69	61	55	49	61	55	49	45	53	48	44	40	33	
取付高さ	器具間隔最大限		2.5	76	69	62	57	72	65	59	54	64	59	54	50	56	52	48	45	37
	横方向 (A)	縦方向 (B)	3.0	79	72	66	61	75	69	63	59	66	61	57	53	59	55	51	48	40
1.5m	2.55 m	1.9 m	4.0	82	77	72	67	78	73	68	64	70	66	62	58	62	59	56	53	44
2	3.41	2.51	5.0	84	80	75	71	80	76	72	68	72	68	65	62	64	61	58	56	47
2.5	4.31	3.12	7.0	87	83	80	76	83	79	76	73	74	72	69	67	66	64	62	60	50
3	5.17	3.74	10.0	89	86	84	81	85	82	80	77	77	74	72	70	69	67	65	64	54

