



東芝照明器具配光データシート

名 称	蛍光灯器具	良	0.73		θ 
形 名	FHT-21007-P H9	中	0.69		
		否	0.61		
光源	名称	蛍光ランプ	効 率	F  22 %	ϕ 
	形名	FHF16EX-N-H			
	光束	2100 lm × 1			
前 面		器具 光束	F  70 %	最大取付間隔	備 考
反射面	塗装 (白)		F  92 %		
			1934 lm		
				A-A	1.6 H
				B-B	1.3 H

光度 (cd/1000lm)				反射率 (%)	天井 壁 床	80						70						50						30		20	0			
$\theta \backslash \phi$	A-A	B-B	C-C			70				50		30		70				50		30		50		30		30		10	0	
						70	50	30	70	50	30	70	50	30	50	30	50	30	30	10	0	30	10	0	30	10	0	30	10	0
						30	10	0	30	10	0	30	10	0	30	10	0	30	10	0	30	10	0	30	10	0	30	10	0	30
室指数				照 明 率 (×0.01)																										
0°				49	45	35	34	27	26	46	43	34	32	26	25	31	29	24	23	22	21	17	14							
10°				59	53	45	42	36	34	55	51	43	40	34	33	38	37	31	30	29	28	23	20							
20°				65	58	51	47	42	40	61	55	49	45	40	38	44	41	37	35	33	32	27	24							
30°				72	64	58	54	49	46	67	61	55	51	47	44	50	47	42	41	38	37	32	28							
40°				77	67	64	58	54	50	72	64	60	55	52	48	54	50	47	44	42	41	35	31							
50°				84	73	73	65	63	58	79	70	68	62	60	56	61	57	54	51	49	47	42	37							
60°				89	76	78	69	69	63	83	73	74	66	66	60	65	60	59	55	53	51	46	41							
70°				92	79	83	72	74	66	86	75	78	69	71	64	69	63	63	59	57	54	49	44							
80°				97	82	89	77	82	72	90	79	83	74	77	69	74	67	69	64	61	58	53	48							
90°				100	84	93	79	86	75	93	81	87	76	81	72	77	70	72	67	64	61	56	51							
100°				106	89	102	86	98	83	99	85	96	82	92	80	84	76	81	74	72	68	64	58							
110°																														
120°																														
130°																														
140°																														
150°																														
160°																														
170°																														
180°																														

