

東芝照明器具配光データシート

名 称	蛍光灯器具	良	0.73	保守率	0.69	0.61	θ 0°	φ	A-A 1.5 H B-B 1.2 H	備考
形 名	FHT-42007-P M9	中	0.69							
名称	蛍光ランプ	否	0.61							
形名	FHF32EX-N-H	F	24%	効 率	64%	88%	器具 光束	6241 lm	最大取付間隔	
光束	3520 lm × 2	F	64%							
		F	88%							
前 面										
反射面	塗装 (白)									

光度 (cd/1000lm)				反射率 (%)	天井				壁				床				照明率 (×0.01)			
θ	φ	A-A	B-B		70	50	30	70	50	30	50	30	50	30	30	10	10	0	0	0
0°		152	152	152	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
10°		151	150	151	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
20°		155	142	149	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
30°		157	128	145	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
40°		154	110	138	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
50°		150	89	126	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
60°		142	65	113	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
70°		119	40	97	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
80°		87	18	65	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
90°		65	5	43	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
100°		91	5	62	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
110°		89	4	56	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
120°		76	4	48	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
130°		67	4	39	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
140°		54	4	29	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
150°		40	4	21	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
160°		20	4	8	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
170°		3	4	4	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
180°		4	4	4	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10

