

東芝照明器具配光データシート


名 称	蛍光灯器具
形 名	FHT-42117MK-PA9

光 源	名称 蛍光ランプ
	形名 FHF32EX-N-H
	光束 4950 lm × 2

前 面	
反射面	塗装（白）

保守率	良 0.73
	中 0.69
	否 0.61

効 率	F  1 %
	F  79 %
	F  80 %
器具光束	7880 lm



最大取付間隔		備考
A-A	1.37 H	
B-B	1.27 H	

光度 (cd/1000lm)			
θ \ ϕ	A-A	B-B	C-C
0°	228	228	228
10°	223	224	225
20°	216	213	216
30°	206	194	202
40°	193	168	181
50°	175	138	158
60°	153	104	131
70°	111	67	100
80°	70	28	57
90°	32	0	20
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井	80						70						50						30			20	0
	壁	70		50		30		70		50		30		50		30		30			10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0			
室指数		照 明 率 (×0.01)																						
0.60		47	43	35	33	28	27	46	42	35	33	28	27	33	32	27	26	27	26	22	21			
0.80		56	51	44	42	37	35	55	50	44	41	36	35	42	40	35	34	34	34	30	28			
1.00		62	56	50	47	42	40	60	54	49	46	42	40	47	45	41	39	39	38	34	33			
1.25		68	61	57	52	49	46	66	59	56	52	48	46	53	50	47	45	45	44	40	38			
1.50		73	64	62	56	54	50	70	62	60	55	53	50	57	54	51	49	49	48	44	42			
2.00		79	69	70	63	63	57	76	68	68	62	61	56	64	60	59	55	56	54	50	49			
2.50		83	72	75	66	68	61	80	70	73	65	66	61	68	63	63	59	61	58	55	53			
3.00		86	74	79	69	73	65	83	73	76	68	71	64	72	66	67	63	64	61	58	56			
4.00		90	77	84	73	79	69	87	75	81	72	77	68	76	70	72	67	69	65	63	61			
5.00		93	78	88	75	83	72	89	77	84	74	80	71	79	72	76	70	72	68	65	64			
10.00		98	82	95	80	92	78	94	81	92	79	89	77	85	77	83	76	78	74	72	70			

