

屋内照明器具特性

品番 (品名)	F S A 2 2 2 1 9 F	
光源	FHF16EX-N-H(2100) ×2	2100.0 l m
管理番号	K0094121(0)DB1	
BZ分類	BZ6/4.5/BZ5	

器具効率	88%	天井	80%				70%				50%				30%				0%		
	上方光束 3%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
下方光束	85%	床		10%				10%				10%				10%				0%	
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.73	0.6	47	35	28	23	45	35	28	23	43	33	27	22	40	32	26	22	20	
	中	0.69	0.8	55	44	37	31	54	43	36	31	51	42	35	31	48	40	34	30	28	
	否	0.61	1.0	61	51	43	37	59	50	42	37	56	48	41	36	53	46	40	36	33	
			1.25	66	57	49	44	64	56	49	43	61	53	47	43	58	51	46	42	39	
下方投影面積	c m ²		1.5	70	61	54	49	68	60	54	48	65	58	52	47	61	56	51	47	44	
等価発光面積	c m ²		2.0	75	68	62	56	73	66	61	56	70	64	59	55	67	62	57	54	51	
取付高さ	器具間隔最大限		2.5	79	72	66	62	77	71	66	61	73	68	64	60	70	66	62	58	55	
	横方向 (A)	縦方向 (B)																			
1.5m	2.11 m	1.95 m	3.0	81	75	70	66	79	74	69	65	76	71	67	64	73	69	65	62	59	
2	2.8	2.56	4.0	84	79	75	71	82	78	74	71	79	75	72	69	76	73	70	67	64	
2.5	3.49	3.17	5.0	86	82	79	75	84	81	77	74	81	78	75	73	78	75	73	71	67	
3	4.2	3.78	7.0	88	85	83	80	87	84	81	79	84	81	79	77	81	79	77	75	72	
			10.0	90	88	86	84	89	87	85	83	86	84	82	81	83	81	80	78	75	

