

■ 東芝照明器具配光データシート


名 称	萤火虫器具
形 名	FT-31101-SL 15

光源	名称	蛍光ランプ
	形名	FL30S・EX-N-H
	光束	2000 lm × 1

前 面	下面開放
反射面	塗装（白）

保守率	良	0.74
	中	0.70
	否	0.61

効 率	F 	4 %
	F 	7 8 %
	F 	8 2 %
	器具 光束	1 6 3 6 lm

	θ 
	ϕ 

最大取付間隔		備考	
A-A	1.4 H		
B-B	1.3 H		

光度 (cd/1000lm)			
$\theta \backslash \phi$	A-A	B-B	C-C
0°	201	201	201
10°	201	198	199
20°	194	188	193
30°	187	172	180
40°	179	151	165
50°	168	125	146
60°	154	95	126
70°	132	61	106
80°	117	23	80
90°	76	0	48
100°	32	0	11
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井	80						70						50						30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		照 明 率 (×0.01)																					
0.60		47	43	34	32	27	26	45	41	33	32	26	26	32	31	25	25	25	24	20	19		
0.80		56	51	43	40	35	34	54	49	42	40	34	33	40	38	33	32	32	31	27	25		
1.00		62	55	49	46	41	39	59	54	48	45	40	38	45	43	38	37	37	36	32	29		
1.25		68	60	56	51	47	44	65	59	54	50	46	44	51	48	44	42	42	41	37	34		
1.50		72	64	61	55	52	48	69	62	59	54	51	48	55	52	49	46	46	45	40	38		
2.00		79	69	69	61	61	55	76	67	66	60	59	55	62	58	56	53	53	51	47	45		
2.50		83	72	74	65	66	60	80	70	71	64	64	59	66	61	61	57	58	55	51	49		
3.00		86	74	78	68	71	63	83	72	75	67	69	62	70	64	65	60	61	58	55	52		
4.00		91	77	84	72	77	68	87	75	80	71	75	67	75	68	70	65	66	63	59	57		
5.00		93	79	87	75	82	71	89	77	84	73	79	70	78	71	74	68	69	66	62	60		
10.00		99	83	95	80	92	78	95	81	91	79	88	77	84	76	82	74	76	72	70	67		

