

東芝照明器具配光データシート

名 称	蛍光灯器具	良	0.74			θ 0°	
形 名	FT-42105K-G L15	中	0.70				
		否	0.61				
光源	名称	蛍光ランプ	効 率	F	1 %	ϕ	
	形名	FL40SS・W/37		F	79 %		
	光束	3100 lm × 2		F	80 %		
前 面			器具 光束	最大取付間隔		備 考	
反射面		塗装 (白)		A-A	1.4 H		
				B-B	1.3 H		

光度 (cd/1000lm)				反 射 率 (%)	天井	80						70						50				30		20	0
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70		50		30		70		50		30		50		30		30		10	0
					床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0
				室指数	照 明 率 (×0.01)																				
0°	228	228	228	0.60	47	43	35	33	28	27	46	42	35	33	28	27	33	32	27	26	27	26	22	21	
10°	223	224	225	0.80	56	51	44	42	37	35	55	50	44	41	36	35	42	40	35	34	34	34	30	28	
20°	216	213	216	1.00	62	56	50	47	42	40	60	54	49	46	42	40	47	45	41	39	39	38	34	33	
30°	206	194	202	1.25	68	61	57	52	49	46	66	59	56	52	48	46	53	50	47	45	45	44	40	38	
40°	193	168	181	1.50	73	64	62	56	54	50	70	62	60	55	53	50	57	54	51	49	49	48	44	42	
50°	175	138	158	2.00	79	69	70	63	63	57	76	68	68	62	61	56	64	60	59	55	56	54	50	49	
60°	153	104	131	2.50	83	72	75	66	68	61	80	70	73	65	66	61	68	63	63	59	61	58	55	53	
70°	111	67	100	3.00	86	74	79	69	73	65	83	73	76	68	71	64	72	66	67	63	64	61	58	56	
80°	70	28	57	4.00	90	77	84	73	79	69	87	75	81	72	77	68	76	70	72	67	69	65	63	61	
90°	32	0	20	5.00	93	78	88	75	83	72	89	77	84	74	80	71	79	72	76	70	72	68	65	64	
100°	0	0	0	10.00	98	82	95	80	92	78	94	81	92	79	89	77	85	77	83	76	78	74	72	70	
110°	0	0	0																						
120°	0	0	0																						
130°	0	0	0																						
140°	0	0	0																						
150°	0	0	0																						
160°	0	0	0																						
170°	0	0	0																						
180°	0	0	0																						

