

東芝照明器具配光データシート

名 称	蛍光灯器具	良	0.74		θ	
形 名	FT-21103NK-SL15	中	0.70			
光 源	名称 蛍光ランプ 形名 FL20SS・ENC/ 18LLN 光束 1550 lm × 1	保守率	否 0.61			
前 面		効 率	F 4 % F 82 % F 86 %	最大取付間隔	備考	
反射面	塗装 (白)	器具光束	1320 lm	A-A 1.43 H B-B 1.27 H		

光度 (cd/1000lm)				反射率 (%)	天井	80						70						50						30		20	0		
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70			50			30			70			50			30			50		30		10	0
					床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0
室指数					照 明 率 (×0.01)																								
0.60					49	45	36	34	28	28	47	44	35	34	28	27	34	32	27	27	26	26	22	20					
0.80					59	53	46	43	37	36	57	52	45	42	37	35	42	40	35	34	34	33	29	27					
1.00					65	58	52	48	43	41	62	57	51	47	42	40	48	45	41	39	39	38	34	32					
1.25					71	63	59	54	50	47	69	62	57	53	49	46	54	51	47	45	45	44	39	37					
1.50					76	67	64	58	55	51	73	65	62	57	54	50	58	55	51	49	49	48	43	41					
2.00					83	72	72	65	64	59	80	70	70	63	62	58	66	61	59	56	56	54	50	48					
2.50					87	75	78	69	70	63	84	73	75	67	68	62	70	65	64	60	61	58	54	52					
3.00					91	78	82	72	75	67	87	76	79	70	72	66	74	68	68	64	65	62	58	55					
4.00					95	81	88	76	81	72	91	79	84	74	79	70	78	72	74	68	69	66	63	60					
5.00					98	83	91	78	86	75	93	81	88	77	83	73	81	74	77	71	73	69	66	63					
10.00					104	87	100	84	96	82	99	85	96	83	93	81	88	80	86	78	80	76	73	71					

