

東芝照明器具配光データシート

名称	直管形LEDランプシステム照明器具
形名	LET-42107NK-LS9

光源	名称	LED (定格出力タイプ)
	形名	LDL40T・N/19/26
	光束	2600 lm × 2

前面	
反射面	塗装 (白)

保守率	良	0.86
	中	0.81
	否	0.72

効率	F ◡	5%
	F ◣	91%
	F ○	96%
	器具光束	4950 lm

最大取付間隔	
A-A	1.3 H
B-B	1.2 H

備考	
----	--

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	275	275	275
10°	267	270	269
20°	256	253	256
30°	242	227	236
40°	221	194	210
50°	198	154	180
60°	168	111	147
70°	129	66	111
80°	86	24	70
90°	50	2	34
100°	39	0	23
110°	19	0	3
120°	1	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井		80				70				50				30		20		0	
	壁	床	70	50	30	10	70	50	30	10	70	50	30	10	70	50	70	50		
室指数	照明率 (×0.01)																			
0.60	56	52	42	40	34	33	54	50	41	39	33	32	40	38	32	32	31	27	25	
0.80	67	61	53	50	44	42	65	60	52	49	43	42	50	47	42	41	40	35	33	
1.00	74	67	60	56	51	48	71	65	59	55	50	48	56	53	48	46	46	45	40	38
1.25	82	72	68	63	59	55	78	71	66	61	57	54	63	59	55	53	53	51	47	44
1.50	86	76	74	67	64	60	83	74	72	66	63	59	67	63	60	57	58	56	51	48
2.00	94	82	83	74	74	68	91	80	81	73	73	67	76	70	69	65	66	63	59	56
2.50	99	85	89	79	81	73	95	83	86	77	79	72	80	74	74	70	71	68	63	61
3.00	103	88	94	82	86	77	98	86	90	80	84	76	84	78	79	73	74	71	67	65
4.00	107	91	100	86	93	82	103	89	96	85	90	81	89	82	85	78	80	76	72	70
5.00	110	93	104	89	98	85	105	91	100	87	95	84	93	84	89	81	83	79	76	73
10.00	116	97	113	95	109	93	111	95	108	93	105	91	100	90	98	89	91	86	83	80

