



東芝照明器具配光データシート

名 称	蛍光灯器具
形 名	FHR-41478NK-PA9

保守率	良	0.73
	中	0.69
	否	0.61



光源	名 称	蛍光ランプ
	形 名	FHF32EX-N-H
	光 束	4950 lm × 1

効 率	F	0 %
	F	84 %
	F	84 %
	器具光束	4136 lm

最大取付間隔	
A-A	1.4 H
B-B	1.3 H

備 考	
-----	--

前 面	下面開放
反射面	塗装（白）

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	265	265	265
10°	266	266	261
20°	262	253	254
30°	256	232	241
40°	239	202	225
50°	199	166	197
60°	135	123	148
70°	64	78	80
80°	20	27	23
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井	80						70						50						30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		照 明 率 (×0.01)																					
0.60		52	47	39	37	32	31	50	46	39	37	32	31	38	36	31	31	31	30	26	25		
0.80		62	56	50	47	42	41	60	55	49	46	42	40	47	45	41	40	40	39	35	34		
1.00		68	61	57	52	49	46	66	60	55	52	48	46	53	50	47	45	46	45	41	39		
1.25		75	67	64	59	56	53	73	65	63	58	55	52	60	56	54	51	52	51	47	45		
1.50		79	70	69	63	61	57	77	69	67	62	60	56	64	60	58	56	57	55	51	49		
2.00		87	75	78	69	71	64	84	74	76	68	69	64	72	67	66	63	64	62	58	57		
2.50		90	78	83	73	76	69	87	77	80	72	74	68	76	70	71	67	68	66	63	61		
3.00		94	80	87	76	81	72	90	79	84	75	79	71	79	73	75	70	72	69	66	64		
4.00		97	83	92	79	87	76	94	82	89	78	85	76	84	77	80	74	76	73	70	69		
5.00		100	84	95	81	91	79	96	83	92	81	88	78	86	79	83	77	79	75	73	71		
10.00		105	87	102	86	99	85	101	86	98	85	96	84	92	83	90	82	85	80	79	77		

