



東芝照明器具配光データシート

名称	蛍光灯器具
形名	FHR-42412NK-PH9

保守率	良	0.73
	中	0.69
	否	0.61



光源	名称	蛍光ランプ
	形名	FHF32EX-N-H
	光束	4950 lm x 2

効率	F	0%
	F	82%
	F	82%
	器具光束	8160 lm

最大取付間隔	
A-A	1.4 H
B-B	1.3 H

備考	
----	--

前面	下面開放
反射面	塗装 (白)

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	257	257	257
10°	257	252	254
20°	252	239	248
30°	241	220	234
40°	222	191	212
50°	190	157	182
60°	145	116	142
70°	92	72	91
80°	32	26	36
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井		80				70				50				30		20		0	
	壁	床	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	30	10
室指数	照明率 (x0.01)																			
0.60	50	46	38	36	31	30	49	45	38	36	31	30	36	35	30	30	30	29	25	24
0.80	61	55	48	45	41	39	59	54	48	45	40	39	46	44	39	38	39	38	34	32
1.00	67	60	55	51	47	45	64	58	54	50	46	44	52	49	45	44	44	43	39	37
1.25	73	65	62	57	54	51	71	64	61	56	53	50	58	55	52	49	50	49	45	43
1.50	77	68	67	61	59	55	75	67	65	60	58	55	62	58	56	54	55	53	49	47
2.00	85	74	75	67	68	62	82	72	73	67	67	62	70	65	64	61	62	60	56	54
2.50	89	76	80	71	74	67	85	75	78	70	72	66	74	68	69	65	66	64	61	59
3.00	92	79	84	74	78	70	88	77	82	73	77	69	77	71	73	68	70	67	64	62
4.00	96	81	90	78	85	74	92	80	87	77	82	74	82	75	78	72	74	71	68	67
5.00	98	83	93	80	89	77	94	82	90	79	86	76	85	77	81	75	77	73	71	70
10.00	103	86	100	84	98	83	99	85	97	83	94	82	90	82	89	80	84	79	77	76

