




東芝照明器具配光データシート

名 称		蛍光灯器具		保守率	良	0.73		θ 			
形 名		FHR-42412NK-PN9			中	0.69			ϕ 		
					否	0.61					
光源	名称	蛍光ランプ		効 率	F 	0 %	最大取付間隔 <table><tr><td>A-A</td><td>1.4 H</td></tr><tr><td>B-B</td><td>1.3 H</td></tr></table>	A-A		1.4 H	B-B
	A-A	1.4 H									
	B-B	1.3 H									
形名	FHF32EX-N-H		F 	85 %							
光束	3520 lm x 2		F 	85 %							
前 面		下面開放		器具光束	5976 lm		備考				
反射面		塗装 (白)									

光度 (cd/1000lm)				反射率 (%)	天井	80						70						50						30			20	0							
$\theta \backslash \phi$	A-A	B-B	C-C			壁	70			50			30			70			50			30			50			30			30			10	0
							30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0	
				室指数		照 明 率 (×0.01)																													
0°				0.60		52	48	40	38	32	31	50	47	39	37	32	31	38	36	31	30	31	30	26	25										
10°				0.80		62	57	50	47	42	40	60	55	49	46	41	40	47	45	41	39	40	39	35	33										
20°				1.00		69	62	57	52	48	46	66	60	55	52	48	46	53	50	46	45	45	44	40	38										
30°				1.25		75	67	64	59	56	52	73	66	62	58	55	52	60	56	53	51	52	50	46	44										
40°				1.50		80	70	69	63	61	57	77	69	67	62	60	56	64	60	58	55	56	54	50	49										
50°				2.00		87	76	78	69	70	64	84	74	76	68	69	64	72	67	66	62	64	61	58	56										
60°				2.50		91	79	83	73	76	69	88	77	81	72	74	68	76	70	71	67	68	66	62	61										
70°				3.00		94	81	87	76	81	72	91	80	84	75	79	71	80	73	75	70	72	69	66	64										
80°				4.00		98	84	92	80	87	77	95	82	90	79	85	76	84	77	81	74	77	73	70	69										
90°				5.00		101	85	96	82	91	79	97	84	93	81	89	79	87	79	84	77	80	76	73	72										
100°				10.00		106	89	103	87	101	85	102	87	100	86	97	85	93	84	91	83	86	81	80	78										
110°																																			
120°																																			
130°																																			
140°																																			
150°																																			
160°																																			
170°																																			
180°																																			

