



東芝照明器具配光データシート

名 称	蛍光灯器具
形 名	FHR-42478NK-PA9

保守率	良	0.73
	中	0.69
	否	0.61



光源	名 称	蛍光ランプ
	形 名	FHF32EX-N-H
	光 束	4950 lm × 2

効 率	F	0 %
	F	82 %
	F	82 %
	器具光束	8159 lm

最大取付間隔	
A-A	1.5 H
B-B	1.3 H

備 考

前 面	下面開放
反射面	塗装（白）

光度 (cd/1000lm)			
θ \ ϕ	A-A	B-B	C-C
0°	229	229	229
10°	230	226	229
20°	229	214	224
30°	226	196	211
40°	219	171	198
50°	204	138	179
60°	179	101	153
70°	121	59	113
80°	52	19	52
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井	80						70						50				30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0
室指数		照 明 率 (×0.01)																			
0.60		49	45	36	35	29	28	47	44	36	34	29	28	35	33	28	28	28	27	23	22
0.80		59	53	46	43	38	37	57	52	45	43	38	36	44	42	37	36	36	35	31	30
1.00		65	58	53	49	44	42	63	57	52	48	44	42	49	47	43	41	42	40	36	35
1.25		72	64	60	55	52	48	69	62	58	54	51	48	56	53	49	47	48	46	42	40
1.50		76	67	65	59	57	53	73	65	63	58	56	52	60	56	54	51	52	50	47	45
2.00		83	72	74	66	66	60	80	71	72	65	65	60	68	63	62	59	60	58	54	52
2.50		87	75	79	70	72	65	84	74	77	69	70	64	72	67	67	63	64	62	58	57
3.00		91	78	83	73	77	68	87	76	81	72	75	68	76	70	71	66	68	65	62	60
4.00		95	80	89	77	83	73	91	79	86	76	81	72	81	74	77	71	73	70	67	65
5.00		97	82	92	79	87	76	94	81	89	78	85	75	84	76	80	74	76	72	70	68
10.00		103	86	100	84	97	82	99	85	96	83	94	82	90	81	88	80	83	78	77	75

