



東芝照明器具配光データシート

名称	蛍光灯器具
形名	FHR-42478NK- -PD9

保守率	良	0.73
	中	0.69
	否	0.61



光源	名称	蛍光ランプ
	形名	FHF32EX-N-H
	光束	4950 lm × 2

効率	F	0%
	F	82%
	F	82%
	器具光束	8159 lm

最大取付間隔	
A-A	1.5 H
B-B	1.3 H

備考	
----	--

前面	下面開放
反射面	塗装 (白)

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	229	229	229
10°	230	226	229
20°	229	214	224
30°	226	196	211
40°	219	171	198
50°	204	138	179
60°	179	101	153
70°	121	59	113
80°	52	19	52
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井		80				70				50				30		20	0		
	壁	床	70	50	30	10	70	50	30	10	70	50	30	10	50	30	10	0		
室指数	照明率 (×0.01)																			
0.60	49	45	36	35	29	28	47	44	36	34	29	28	35	33	28	28	28	27	23	22
0.80	59	53	46	43	38	37	57	52	45	43	38	36	44	42	37	36	36	35	31	30
1.00	65	58	53	49	44	42	63	57	52	48	44	42	49	47	43	41	42	40	36	35
1.25	72	64	60	55	52	48	69	62	58	54	51	48	56	53	49	47	48	46	42	40
1.50	76	67	65	59	57	53	73	65	63	58	56	52	60	56	54	51	52	50	47	45
2.00	83	72	74	66	66	60	80	71	72	65	65	60	68	63	62	59	60	58	54	52
2.50	87	75	79	70	72	65	84	74	77	69	70	64	72	67	67	63	64	62	58	57
3.00	91	78	83	73	77	68	87	76	81	72	75	68	76	70	71	66	68	65	62	60
4.00	95	80	89	77	83	73	91	79	86	76	81	72	81	74	77	71	73	70	67	65
5.00	97	82	92	79	87	76	94	81	89	78	85	75	84	76	80	74	76	72	70	68
10.00	103	86	100	84	97	82	99	85	96	83	94	82	90	81	88	80	83	78	77	75

