



東芝照明器具配光データシート

名称	蛍光灯器具
形名	FHR-42713N- PK9

保守率	良	0.73
	中	0.69
	否	0.61



光源	名称	メロウライン
	形名	FHF32EX-N-H
	光束	4950 lm × 2

効率	F	0%
	F	72%
	F	72%
	器具光束	7116 lm

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備考	
----	--

前面	
反射面	塗装 (白)

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	271	270	271
10°	262	269	270
20°	255	256	260
30°	237	235	242
40°	192	206	211
50°	124	171	160
60°	61	130	94
70°	33	83	40
80°	13	31	15
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井		80				70				50				30		20	0		
	壁	床	70	50	30	10	70	50	30	10	70	50	30	10	70	50	10	0		
室指数	照明率 (×0.01)																			
0.60	47	43	37	35	31	30	45	42	36	34	30	30	35	34	30	29	29	29	26	25
0.80	56	51	46	43	40	38	54	50	45	43	39	38	44	42	38	37	38	37	34	32
1.00	61	55	51	48	45	43	59	54	50	47	44	42	49	46	43	42	42	41	38	37
1.25	66	59	57	53	51	48	64	58	56	52	50	47	54	51	49	47	48	46	43	42
1.50	70	62	62	56	55	51	68	61	60	55	54	51	58	54	53	50	51	49	47	45
2.00	76	66	69	61	63	57	73	65	67	60	62	57	64	59	59	56	57	55	52	51
2.50	79	68	73	64	67	61	76	67	71	63	66	60	67	62	63	59	61	58	56	54
3.00	81	70	76	66	71	63	79	69	74	65	69	63	70	64	66	62	63	61	58	57
4.00	84	72	80	69	76	67	81	71	77	68	74	66	73	67	70	65	67	64	62	60
5.00	86	73	82	71	79	69	83	72	80	70	77	68	75	68	73	67	69	65	64	62
10.00	90	75	88	74	86	73	87	74	85	73	83	72	79	72	78	71	73	69	68	67

