



東芝照明器具配光データシート

名称	蛍光灯器具
形名	FHR-42860N-PA9

保守率	良	0.73
	中	0.69
	否	0.61



光源	名称	蛍光ランプ
	形名	FHF32EX-N-H
	光束	4950 lm × 2

効率	F	0%
	F	80%
	F	80%
	器具光束	7935 lm

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備考	
----	--

前面	下面開放
反射面	塗装 (白)

光度 (cd/1000lm)			
θ	A-A	B-B	C-C
0°	291	291	291
10°	291	286	289
20°	284	274	282
30°	257	253	262
40°	223	224	226
50°	172	188	184
60°	76	144	127
70°	27	93	40
80°	9	35	11
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井		80				70				50				30		20		0	
	壁	床	70	50	30	10	70	50	30	10	70	50	30	10	50	30	30	10	10	0
室指数	照明率 (×0.01)																			
0.60	51	47	40	38	34	33	50	46	40	38	33	32	39	37	33	32	32	32	28	27
0.80	62	56	51	48	44	42	60	55	50	47	43	42	48	46	42	41	41	41	37	36
1.00	68	61	57	53	50	47	66	60	56	52	49	47	54	51	48	46	47	46	42	41
1.25	74	66	64	58	57	53	72	64	62	58	56	53	60	56	54	52	53	51	48	46
1.50	78	69	68	62	62	57	75	67	67	61	61	57	64	60	59	56	57	55	52	50
2.00	84	73	76	68	70	64	82	72	74	67	69	63	71	66	66	62	64	61	58	57
2.50	88	76	81	72	75	68	85	75	79	71	74	67	75	69	70	66	68	65	62	61
3.00	91	78	84	74	79	71	88	77	82	73	77	70	78	71	74	69	71	68	65	64
4.00	94	80	89	77	85	74	91	79	86	76	83	74	81	75	78	72	75	71	69	67
5.00	96	81	92	79	88	77	93	80	89	78	86	76	84	76	81	75	77	73	71	70
10.00	101	84	98	83	96	82	97	83	95	82	93	81	89	80	87	79	82	78	76	75

