



# 東芝照明器具配光データシート

名称	蛍光灯器具
形名	FHR-42860N-PM9

保守率	良	0.73
	中	0.69
	否	0.61



光源	名称	蛍光ランプ
	形名	FHF32EX-N-H
	光束	3520 lm x 2

効率	F	0%
	F	80%
	F	80%
	器具光束	5642 lm

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備考	
----	--

前面	下面開放
反射面	塗装(白)

光度 (cd/1000lm)			
$\theta$	A-A	B-B	C-C
0°	291	291	291
10°	291	286	289
20°	284	274	282
30°	257	253	262
40°	223	224	226
50°	172	188	184
60°	76	144	127
70°	27	93	40
80°	9	35	11
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井		80				70				50				30		20	0	
	壁	床	70	50	30	10	70	50	30	10	70	50	30	10	50	30	30	10	
室指数	照明率 (x0.01)																		
0.60	51	47	40	38	34	33	50	46	40	38	33	32	39	37	33	32	32	28	27
0.80	62	56	51	48	44	42	60	55	50	47	43	42	48	46	42	41	41	37	36
1.00	68	61	57	53	50	47	66	60	56	52	49	47	54	51	48	46	47	46	41
1.25	74	66	64	58	57	53	72	64	62	58	56	53	60	56	54	52	53	51	48
1.50	78	69	68	62	62	57	75	67	67	61	61	57	64	60	59	56	57	55	52
2.00	84	73	76	68	70	64	82	72	74	67	69	63	71	66	66	62	64	61	58
2.50	88	76	81	72	75	68	85	75	79	71	74	67	75	69	70	66	68	65	62
3.00	91	78	84	74	79	71	88	77	82	73	77	70	78	71	74	69	71	68	65
4.00	94	80	89	77	85	74	91	79	86	76	83	74	81	75	78	72	75	71	69
5.00	96	81	92	79	88	77	93	80	89	78	86	76	84	76	81	75	77	73	71
10.00	101	84	98	83	96	82	97	83	95	82	93	81	89	80	87	79	82	78	76

