



東芝照明器具配光データシート

名称	蛍光灯器具
形名	FHR-44770-P H9

保守率	良	0.73
	中	0.69
	否	0.61



光源	名称	蛍光ランプ
	形名	FHF32EX-N-H
	光束	4950 lm x 4

効率	F	0%
	F	69%
	F	69%
	器具光束	13586 lm

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備考	
----	--

前面	
反射面	塗装 (白)

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	257	257	257
10°	255	252	254
20°	250	241	246
30°	237	222	231
40°	199	196	207
50°	124	164	162
60°	51	126	90
70°	22	81	30
80°	7	32	9
90°	0	0	1
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井		80				70				50				30		20	0		
	壁	床	70	50	30	10	70	50	30	10	70	50	30	10	50	30	30	10		
室指数	照明率 (x0.01)																			
0.60	45	41	35	33	29	28	43	40	35	33	29	28	34	32	29	28	28	25	24	
0.80	53	48	44	41	38	36	52	48	43	41	38	36	42	40	37	36	36	35	32	31
1.00	58	52	49	46	43	41	57	51	48	45	43	41	47	44	42	40	41	40	37	35
1.25	64	57	55	51	49	46	62	55	54	50	48	46	52	49	47	45	46	44	42	40
1.50	67	59	59	54	53	49	65	58	58	53	52	49	55	52	51	48	49	48	45	44
2.00	73	63	66	59	60	55	70	62	64	58	59	55	61	57	57	54	55	53	51	49
2.50	76	65	70	61	65	58	73	64	68	61	63	58	64	59	61	57	58	56	54	52
3.00	78	67	73	64	68	61	75	66	70	63	67	60	67	61	64	59	61	58	56	55
4.00	81	69	76	66	73	64	78	68	74	65	71	63	70	64	67	62	64	61	59	58
5.00	82	70	79	68	76	66	79	69	76	67	73	65	72	65	70	64	66	63	61	60
10.00	86	72	84	71	82	70	83	71	81	70	79	69	76	68	75	68	70	66	65	64

