



東芝照明器具配光データシート

名称	蛍光灯器具
形名	FHR-44771-P H9

保守率	良	0.73
	中	0.69
	否	0.61



光源	名称	蛍光ランプ
	形名	FHF32EX-N-H
	光束	4950 lm x 4

効率	F	0%
	F	66%
	F	66%
	器具光束	13047 lm

最大取付間隔	
A-A	1.3 H
B-B	1.2 H

備考	
----	--

前面	ルーバー
反射面	塗装 (白)

光度 (cd/1000lm)			
θ	A-A	B-B	C-C
0°	268	268	268
10°	266	260	263
20°	260	241	249
30°	247	214	228
40°	207	181	198
50°	130	143	149
60°	56	101	82
70°	25	54	31
80°	8	16	12
90°	0	0	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井		80				70				50				30		20		0	
	壁	床	70	50	30	10	70	50	30	10	70	50	30	10	50	30	30	10	10	0
室指数	照明率 (x0.01)																			
0.60	44	40	35	33	29	28	42	39	34	33	29	28	33	32	29	28	28	28	25	24
0.80	52	47	43	41	38	36	51	46	43	40	37	36	41	39	37	35	36	35	32	31
1.00	57	51	48	45	43	40	55	50	47	44	42	40	46	43	41	40	40	39	36	35
1.25	62	55	54	49	48	45	60	54	53	49	47	45	51	48	46	44	45	44	41	40
1.50	65	57	58	52	52	48	63	56	56	52	51	48	54	50	50	47	48	47	44	43
2.00	70	61	64	57	59	54	68	60	62	56	58	53	59	55	56	52	54	52	49	48
2.50	73	63	67	59	63	57	71	62	66	59	61	56	62	58	59	55	57	54	52	51
3.00	75	64	70	61	66	59	73	63	68	61	64	58	65	59	62	57	59	56	54	53
4.00	78	66	74	64	70	62	75	65	72	63	68	61	67	62	65	60	62	59	57	56
5.00	79	67	76	65	73	63	77	66	74	64	71	63	69	63	67	62	64	61	59	58
10.00	83	69	81	68	79	67	80	68	78	67	76	66	73	66	72	65	68	64	63	61

