

屋内照明器具特性

品番 (品名)	NNF 40903														
光源	LED3000_85_2280 x1 2280.0 1 m														
管理番号	K0172825 (0) DR 1														
BZ分類	BZ6														

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	20 %	室指数	照明率 (X0.01)																ZCM		
下方光束	80 %																				
保守率	良 中 否	0.83	0.6	51	39	31	25	49	37	30	25	44	35	28	23	40	32	26	22	19	
		0.81	0.8	60	48	40	34	58	47	39	33	53	43	37	32	48	40	34	30	26	
		0.77	1.0	67	55	47	41	64	53	46	40	58	49	43	38	53	46	40	36	31	
			1.25	73	62	54	48	69	60	52	47	63	55	49	44	58	51	46	42	37	
下方投影面積	c m ²	1.5	77	67	59	53	73	64	58	52	67	60	54	49	61	55	50	46	41		
		2.0	82	74	67	62	79	71	65	60	72	66	61	56	66	61	57	53	47		
取付高さ	器具間隔最大限		2.5	86	79	73	67	82	76	70	65	76	70	66	62	69	65	61	58	51	
	横方向 (A)	縦方向 (B)	3.0	89	82	77	72	85	79	74	70	78	73	69	65	72	68	65	61	55	
1.5m	2.2 m	1.97 m	4.0	92	87	82	78	88	84	79	75	82	78	74	71	75	72	69	66	59	
2	2.9	2.54	5.0	94	90	85	82	90	86	83	79	84	80	77	74	77	75	72	70	62	
2.5	3.61	3.12	7.0	96	93	90	87	93	90	87	84	86	84	81	79	80	78	76	74	66	
3	4.33	3.72	10.0	98	96	93	91	95	93	90	88	88	86	84	83	82	80	79	77	69	

