

屋内照明器具特性

品番 (品名)	NNF 4 1 2 0 1									
光源	LED4000_85_3160 x1 3160.0 lm									
管理番号	K0172825 (0) DR 1									
BZ分類	BZ6									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	20 %	反射率	床	10 %				10 %				10 %				10 %				0 %
下方光束	80 %		室指数	照明率 (X0.01)																ZCM
保守率	良 中 否	0.83	0.6	51	39	31	25	49	37	30	25	44	35	28	23	40	32	26	22	19
		0.81	0.8	60	48	40	34	58	47	39	33	53	43	37	32	48	40	34	30	26
			1.0	67	55	47	41	64	53	46	40	58	49	43	38	53	46	40	36	31
		0.77	1.25	73	62	54	48	69	60	52	47	63	55	49	44	58	51	46	42	37
下方投影面積	c m ²	1.5	77	67	59	53	73	64	58	52	67	60	54	49	61	55	50	46	41	
		2.0	82	74	67	62	79	71	65	60	72	66	61	56	66	61	57	53	47	
取付高さ	器具間隔最大限		2.5	86	79	73	67	82	76	70	65	76	70	66	62	69	65	61	58	51
	横方向 (A)	縦方向 (B)	3.0	89	82	77	72	85	79	74	70	78	73	69	65	72	68	65	61	55
1.5m	2.22 m	2.09 m	4.0	92	87	82	78	88	84	79	75	82	78	74	71	75	72	69	66	59
2	2.93	2.63	5.0	94	90	85	82	90	86	83	79	84	80	77	74	77	75	72	70	62
2.5	3.64	3.19	7.0	96	93	90	87	93	90	87	84	86	84	81	79	80	78	76	74	66
3	4.34	3.77	10.0	98	96	93	91	95	93	90	88	88	86	84	83	82	80	79	77	69

