

屋内照明器具特性	
品番 (品名)	NNN55050
光源	LED5000_85_3300 ×1 3300.0 lm
管理番号	K0172825 (0) DR 1
BZ分類	BZ6

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z
保守率		良 中 否	0.83	0.6	51	39	31	25	49	37	30	25	44	35	28	23	40	32	26	22	19
			0.81	0.8	60	48	40	34	58	47	39	33	53	43	37	32	48	40	34	30	26
			0.77	1.0	67	55	47	41	64	53	46	40	58	49	43	38	53	46	40	36	31
				1.25	73	62	54	48	69	60	52	47	63	55	49	44	58	51	46	42	37
下方投影面積		cm ²		1.5	77	67	59	53	73	64	58	52	67	60	54	49	61	55	50	46	41
			等価発光面積	cm ²	2.0	82	74	67	62	79	71	65	60	72	66	61	56	66	61	57	53
取付 高さ	器具間隔最大限		2.5	86	79	73	67	82	76	70	65	76	70	66	62	69	65	61	58	51	
	横方向 (A)	縦方向 (B)	3.0	89	82	77	72	85	79	74	70	78	73	69	65	72	68	65	61	55	
1.5m	2.22 m	2.09 m	4.0	92	87	82	78	88	84	79	75	82	78	74	71	75	72	69	66	59	
2	2.93	2.63	5.0	94	90	85	82	90	86	83	79	84	80	77	74	77	75	72	70	62	
2.5	3.64	3.19	7.0	96	93	90	87	93	90	87	84	86	84	81	79	80	78	76	74	66	
3	4.34	3.77	10.0	98	96	93	91	95	93	90	88	88	86	84	83	82	80	79	77	69	

