

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | NNN55051                     |
| 光源       | LED4000_85_3160 ×1 3160.0 lm |
| 管理番号     | K0172825 ( 0 ) DR 1          |
| BZ分類     | BZ6                          |

| 器具効率             |                 | 100 %<br><br>上方光束<br>20 %<br>下方光束<br>80 % | 反射率  | 天井   | 80 %               |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|------------------|-----------------|-------------------------------------------|------|------|--------------------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|
|                  |                 |                                           |      | 壁    | 70                 | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|                  |                 |                                           |      | 床    | 10 %               |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|                  |                 |                                           |      | 室指数  | 照明率 ( X0.01 ) Z CM |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |
| 保守率              |                 | 良<br>中<br>否                               | 0.83 | 0.6  | 51                 | 39 | 31 | 25 | 49   | 37 | 30 | 25 | 44   | 35 | 28 | 23 | 40   | 32 | 26 | 22 | 19  |
|                  |                 |                                           | 0.81 | 0.8  | 60                 | 48 | 40 | 34 | 58   | 47 | 39 | 33 | 53   | 43 | 37 | 32 | 48   | 40 | 34 | 30 | 26  |
|                  |                 |                                           | 0.77 | 1.0  | 67                 | 55 | 47 | 41 | 64   | 53 | 46 | 40 | 58   | 49 | 43 | 38 | 53   | 46 | 40 | 36 | 31  |
|                  |                 |                                           |      | 1.25 | 73                 | 62 | 54 | 48 | 69   | 60 | 52 | 47 | 63   | 55 | 49 | 44 | 58   | 51 | 46 | 42 | 37  |
| 下方投影面積<br>等価発光面積 |                 | cm <sup>2</sup><br>cm <sup>2</sup>        |      | 1.5  | 77                 | 67 | 59 | 53 | 73   | 64 | 58 | 52 | 67   | 60 | 54 | 49 | 61   | 55 | 50 | 46 | 41  |
|                  |                 |                                           |      | 2.0  | 82                 | 74 | 67 | 62 | 79   | 71 | 65 | 60 | 72   | 66 | 61 | 56 | 66   | 61 | 57 | 53 | 47  |
| 取付<br>高さ         | 器具間隔最大限         |                                           |      | 2.5  | 86                 | 79 | 73 | 67 | 82   | 76 | 70 | 65 | 76   | 70 | 66 | 62 | 69   | 65 | 61 | 58 | 51  |
|                  | 横方向 (A) 縦方向 (B) |                                           |      | 3.0  | 89                 | 82 | 77 | 72 | 85   | 79 | 74 | 70 | 78   | 73 | 69 | 65 | 72   | 68 | 65 | 61 | 55  |
| 1.5m             | 2.22 m          | 2.09 m                                    |      | 4.0  | 92                 | 87 | 82 | 78 | 88   | 84 | 79 | 75 | 82   | 78 | 74 | 71 | 75   | 72 | 69 | 66 | 59  |
| 2                | 2.93            | 2.63                                      |      | 5.0  | 94                 | 90 | 85 | 82 | 90   | 86 | 83 | 79 | 84   | 80 | 77 | 74 | 77   | 75 | 72 | 70 | 62  |
| 2.5              | 3.64            | 3.19                                      |      | 7.0  | 96                 | 93 | 90 | 87 | 93   | 90 | 87 | 84 | 86   | 84 | 81 | 79 | 80   | 78 | 76 | 74 | 66  |
| 3                | 4.34            | 3.77                                      |      | 10.0 | 98                 | 96 | 93 | 91 | 95   | 93 | 90 | 88 | 88   | 86 | 84 | 83 | 82   | 80 | 79 | 77 | 69  |

