

屋内照明器具特性

品番 (品名)	NNN56053															
光源	LED3000_85_4430 x1 4430.0 1m															
管理番号	K0172825(0)DR1															
BZ分類	BZ6															

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	20%	室指数	照明率 (X0.01)																ZCM		
下方光束	80%																				
保守率	良 中 否	0.83	0.6	51	39	31	25	49	37	30	25	44	35	28	23	40	32	26	22	19	
		0.81	0.8	60	48	40	34	58	47	39	33	53	43	37	32	48	40	34	30	26	
			1.0	67	55	47	41	64	53	46	40	58	49	43	38	53	46	40	36	31	
		0.77	1.25	73	62	54	48	69	60	52	47	63	55	49	44	58	51	46	42	37	
下方投影面積	c m ²	1.5	77	67	59	53	73	64	58	52	67	60	54	49	61	55	50	46	41		
		2.0	82	74	67	62	79	71	65	60	72	66	61	56	66	61	57	53	47		
取付高さ	器具間隔最大限		2.5	86	79	73	67	82	76	70	65	76	70	66	62	69	65	61	58	51	
	横方向 (A)	縦方向 (B)	3.0	89	82	77	72	85	79	74	70	78	73	69	65	72	68	65	61	55	
1.5m	2.22m	2.09m	4.0	92	87	82	78	88	84	79	75	82	78	74	71	75	72	69	66	59	
2	2.93	2.63	5.0	94	90	85	82	90	86	83	79	84	80	77	74	77	75	72	70	62	
2.5	3.64	3.19	7.0	96	93	90	87	93	90	87	84	86	84	81	79	80	78	76	74	66	
3	4.34	3.77	10.0	98	96	93	91	95	93	90	88	88	86	84	83	82	80	79	77	69	

