

屋内照明器具特性	
品番 (品名)	XLW2 1 2 DENZ
光源	LED5000_85_1520 ×1 1520.0 lm
管理番号	K0141082 ( 1 ) DB 1
BZ分類	BZ5

器具効率		100 %		反射率	天井	80 %					70 %					50 %					30 %					0 %
					壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
					床	10 %					10 %					10 %					10 %					0 %
					照明率 ( X0.01 ) ZCM																					
保守率		良 中 否	0.83	0.6	55	42	35	29	53	42	34	29	50	40	33	28	48	39	32	28	26					
			0.81	0.8	65	53	45	39	63	52	44	38	59	50	43	38	56	48	42	37	35					
			0.77	1.0	71	60	52	46	69	59	51	46	65	57	50	45	62	54	49	44	41					
				1.25	77	67	59	53	75	65	58	53	71	63	57	52	67	61	55	51	48					
下方投影面積		cm <sup>2</sup>		1.5	81	72	64	59	79	70	64	58	75	68	62	57	71	65	60	56	52					
			等価発光面積	cm <sup>2</sup>	2.0	87	79	72	67	84	77	71	66	80	74	69	65	77	71	67	63	60				
取付 高さ	器具間隔最大限			2.5	90	83	78	73	88	82	76	72	84	79	74	70	80	76	72	68	65					
	横方向 ( A )		縦方向 ( B )	3.0	93	87	81	77	91	85	80	76	87	82	78	74	83	79	75	72	68					
1.5m	1.93 m	1.9 m	4.0	96	91	87	83	94	89	85	82	90	86	83	80	86	83	80	78	74						
2	2.57	2.51	5.0	98	94	90	87	96	92	89	86	92	89	86	83	88	86	83	81	77						
2.5	3.22	3.12	7.0	100	97	94	92	98	95	93	90	95	92	90	88	91	89	87	85	81						
3	3.84	3.72	10.0	102	100	98	96	100	98	96	94	97	95	93	91	93	92	90	89	84						

