

屋内照明器具特性

品番 (品名)	XLW4 1 3 KENZ	
光源	LED5000_85_1870 x1	1870.0 lm
管理番号	K0141080 (1) DB 1	
BZ分類	BZ5 / 1.4 / BZ4	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	100 %	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.81	0.6	5.7	4.5	3.7	3.1	5.6	4.4	3.7	3.1	5.3	4.3	3.6	3.1	5.1	4.2	3.6	3.1	2.9
	中	0.77	0.8	6.7	5.6	4.8	4.2	6.6	5.5	4.7	4.2	6.3	5.4	4.7	4.2	6.0	5.2	4.6	4.2	3.9
	否	0.68	1.0	7.4	6.3	5.6	5.0	7.2	6.2	5.5	5.0	6.9	6.1	5.4	4.9	6.7	5.9	5.3	4.9	4.7
			1.25	8.0	7.0	6.3	5.8	7.8	6.9	6.3	5.7	7.5	6.8	6.2	5.7	7.2	6.6	6.1	5.6	5.4
下方投影面積	c m ²		1.5	8.4	7.5	6.9	6.3	8.2	7.4	6.8	6.3	7.9	7.3	6.7	6.2	7.7	7.1	6.6	6.2	5.9
	等価発光面積		c m ²	2.0	9.0	8.3	7.7	7.2	8.8	8.2	7.6	7.1	8.5	7.9	7.5	7.1	8.2	7.8	7.3	7.0
取付高さ	器具間隔最大限		2.5	9.3	8.7	8.2	7.8	9.2	8.6	8.1	7.7	8.9	8.4	8.0	7.6	8.6	8.2	7.8	7.5	7.3
	横方向 (A)	縦方向 (B)	3.0	9.6	9.1	8.6	8.2	9.4	8.9	8.5	8.1	9.1	8.7	8.4	8.0	8.9	8.5	8.2	7.9	7.7
1.5m	1.97 m	2.1 m	4.0	9.9	9.5	9.1	8.8	9.7	9.4	9.0	8.7	9.5	9.1	8.8	8.6	9.2	8.9	8.7	8.4	8.2
2	2.6	2.67	5.0	10.1	9.7	9.4	9.1	9.9	9.6	9.3	9.1	9.7	9.4	9.1	8.9	9.4	9.2	9.0	8.8	8.5
2.5	3.24	3.24	7.0	10.3	10.0	9.8	9.6	10.1	9.9	9.7	9.5	9.9	9.7	9.5	9.3	9.6	9.5	9.3	9.2	8.9
3	3.87	3.84	10.0	10.4	10.3	10.1	9.9	10.3	10.1	10.0	9.8	10.1	9.9	9.8	9.7	9.8	9.7	9.6	9.5	9.2

