

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | XLX210NEN                    |
| 光源       | LED5000_85_1600 ×1 1600.0 lm |
| 管理番号     | K0135074 (2) DB1             |
| BZ分類     | BZ5                          |

| 器具効率     |           | 100 %           | 反射率    | 天井            | 80 %            |     |    |     | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |    |    |   |  |   |
|----------|-----------|-----------------|--------|---------------|-----------------|-----|----|-----|------|----|----|----|------|----|----|----|------|----|----|----|-----|----|----|---|--|---|
|          |           |                 |        | 壁             | 70              | 50  | 30 | 10  | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |    |    |   |  |   |
|          |           |                 |        | 床             | 10 %            |     |    |     | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |    |    |   |  |   |
| 上方光束     |           | 4 %             | 室指数    | 照明率 ( X0.01 ) |                 |     |    |     |      |    |    |    |      |    |    |    |      |    |    |    |     |    | Z  | C |  | M |
| 下方光束     |           | 96 %            |        |               |                 |     |    |     |      |    |    |    |      |    |    |    |      |    |    |    |     |    |    |   |  |   |
| 保守率      |           | 良<br>中<br>否     | 0.83   | 0.6           | 56              | 44  | 36 | 30  | 54   | 43 | 36 | 30 | 52   | 42 | 35 | 30 | 49   | 40 | 34 | 30 | 27  |    |    |   |  |   |
|          |           |                 | 0.81   | 0.8           | 66              | 54  | 46 | 41  | 64   | 53 | 46 | 40 | 61   | 51 | 45 | 40 | 58   | 50 | 44 | 39 | 37  |    |    |   |  |   |
|          |           |                 | 0.77   | 1.0           | 72              | 61  | 54 | 48  | 70   | 60 | 53 | 47 | 67   | 58 | 52 | 47 | 64   | 56 | 51 | 46 | 43  |    |    |   |  |   |
|          |           |                 |        | 1.25          | 78              | 68  | 61 | 55  | 76   | 67 | 60 | 55 | 72   | 65 | 59 | 54 | 69   | 62 | 57 | 53 | 50  |    |    |   |  |   |
| 下方投影面積   |           | cm <sup>2</sup> |        | 1.5           | 82              | 73  | 66 | 60  | 80   | 72 | 65 | 60 | 76   | 69 | 64 | 59 | 73   | 67 | 62 | 58 | 55  |    |    |   |  |   |
|          |           |                 | 等価発光面積 |               | cm <sup>2</sup> | 2.0 | 88 | 80  | 74   | 69 | 86 | 79 | 73   | 68 | 82 | 76 | 71   | 67 | 78 | 73 | 69  | 65 | 62 |   |  |   |
| 取付<br>高さ | 器具間隔最大限   |                 | 2.5    | 91            | 85              | 79  | 74 | 89  | 83   | 78 | 73 | 85 | 80   | 76 | 72 | 82 | 77   | 74 | 70 | 67 |     |    |    |   |  |   |
|          | 横方向 ( A ) | 縦方向 ( B )       | 3.0    | 94            | 88              | 83  | 78 | 92  | 86   | 82 | 78 | 88 | 83   | 79 | 76 | 84 | 81   | 77 | 74 | 71 |     |    |    |   |  |   |
| 1.5m     | 1.9 m     | 1.89 m          | 4.0    | 97            | 92              | 88  | 84 | 95  | 90   | 87 | 83 | 91 | 87   | 84 | 81 | 88 | 85   | 82 | 79 | 76 |     |    |    |   |  |   |
| 2        | 2.53      | 2.49            | 5.0    | 99            | 95              | 91  | 88 | 97  | 93   | 90 | 87 | 93 | 90   | 87 | 85 | 90 | 87   | 85 | 83 | 79 |     |    |    |   |  |   |
| 2.5      | 3.16      | 3.09            | 7.0    | 101           | 98              | 95  | 93 | 99  | 96   | 94 | 91 | 96 | 93   | 91 | 89 | 92 | 90   | 88 | 87 | 83 |     |    |    |   |  |   |
| 3        | 3.8       | 3.69            | 10.0   | 103           | 101             | 98  | 96 | 101 | 99   | 97 | 95 | 97 | 96   | 94 | 93 | 94 | 93   | 91 | 90 | 86 |     |    |    |   |  |   |

