

| 屋内照明器具特性 |                             |
|----------|-----------------------------|
| 品番 (品名)  | XLX410AENT                  |
| 光源       | LED5000_85_2000 ×1 2000.0lm |
| 管理番号     | K0128261 ( * ) DB 1         |
| BZ分類     | BZ5                         |

| 器具効率     |           | 100 %           | 反射率    | 天井              | 80 % |    |    |     | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |    |   |    |
|----------|-----------|-----------------|--------|-----------------|------|----|----|-----|------|----|----|----|------|----|----|----|------|----|----|----|-----|----|---|----|
|          |           |                 |        | 壁               | 70   | 50 | 30 | 10  | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |    |   |    |
|          |           |                 |        | 床               | 10 % |    |    |     | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |    |   |    |
| 上方光束     |           | 4 %             | 室指数    | 照明率 ( X0.01 )   |      |    |    |     |      |    |    |    |      |    |    |    |      |    |    |    |     |    | Z | CM |
| 下方光束     |           | 96 %            |        |                 |      |    |    |     |      |    |    |    |      |    |    |    |      |    |    |    |     |    |   |    |
| 保守率      |           | 良<br>中<br>否     | 0.83   | 0.6             | 55   | 42 | 34 | 29  | 53   | 41 | 34 | 28 | 50   | 40 | 33 | 28 | 48   | 39 | 32 | 28 | 25  |    |   |    |
|          |           |                 | 0.81   | 0.8             | 64   | 53 | 44 | 38  | 63   | 52 | 44 | 38 | 59   | 50 | 43 | 38 | 56   | 48 | 42 | 37 | 35  |    |   |    |
|          |           |                 | 0.77   | 1.0             | 71   | 60 | 52 | 46  | 69   | 59 | 51 | 45 | 65   | 56 | 50 | 45 | 62   | 54 | 49 | 44 | 41  |    |   |    |
|          |           |                 |        | 1.25            | 77   | 67 | 59 | 53  | 75   | 65 | 58 | 52 | 71   | 63 | 57 | 52 | 68   | 61 | 55 | 51 | 48  |    |   |    |
| 下方投影面積   |           | cm <sup>2</sup> |        | 1.5             | 81   | 72 | 64 | 58  | 79   | 70 | 63 | 58 | 75   | 68 | 62 | 57 | 71   | 65 | 60 | 56 | 53  |    |   |    |
|          |           |                 | 等価発光面積 | cm <sup>2</sup> | 2.0  | 87 | 79 | 72  | 67   | 85 | 77 | 71 | 66   | 81 | 74 | 69 | 65   | 77 | 72 | 67 | 63  | 60 |   |    |
| 取付<br>高さ | 器具間隔最大限   |                 | 2.5    | 90              | 83   | 77 | 72 | 88  | 82   | 76 | 72 | 84 | 79   | 74 | 70 | 81 | 76   | 72 | 69 | 65 |     |    |   |    |
|          | 横方向 ( A ) | 縦方向 ( B )       | 3.0    | 93              | 87   | 81 | 77 | 91  | 85   | 80 | 76 | 87 | 82   | 78 | 74 | 83 | 79   | 76 | 73 | 69 |     |    |   |    |
| 1.5m     | 2m        | 2.19m           | 4.0    | 96              | 91   | 87 | 83 | 94  | 90   | 85 | 82 | 90 | 86   | 83 | 80 | 87 | 83   | 81 | 78 | 74 |     |    |   |    |
| 2        | 2.64      | 2.76            | 5.0    | 98              | 94   | 90 | 87 | 96  | 92   | 89 | 86 | 92 | 89   | 86 | 83 | 89 | 86   | 84 | 81 | 78 |     |    |   |    |
| 2.5      | 3.29      | 3.35            | 7.0    | 101             | 97   | 94 | 92 | 99  | 96   | 93 | 90 | 95 | 93   | 90 | 88 | 92 | 89   | 88 | 86 | 82 |     |    |   |    |
| 3        | 3.93      | 3.96            | 10.0   | 102             | 100  | 98 | 96 | 101 | 98   | 96 | 94 | 97 | 95   | 93 | 92 | 94 | 92   | 91 | 89 | 85 |     |    |   |    |

