

東芝ランプ 配光データシート

名称	東芝LED電球
形名	LDA16L-G/10OW
光束	1520 lm × 1

保守率	良	1.00
	中	1.00
	否	1.00



効率	F	%
	F	%
	F	100 %
	器具光束	1520 lm

最大取付間隔	
A-A	1.5 H
B-B	1.5 H

備考

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	123		
10°	123		
20°	121		
30°	119		
40°	117		
50°	113		
60°	108		
70°	102		
80°	94		
90°	85		
100°	75		
110°	65		
120°	54		
130°	44		
140°	34		
150°	26		
160°	20		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30		20		0
	壁	70	50	30	70	50	30	70	50	30	50	30	50	30	30	10	0							
床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0							
室指数	照明率 (×0.01)																							
0.60	51	47	37	35	28	27	47	44	34	33	26	25	30	29	23	23	20	20	15	12				
0.80	61	56	46	43	36	35	57	52	43	41	34	33	38	36	30	30	27	26	21	17				
1.00	68	61	53	49	43	40	63	57	49	46	40	38	43	41	36	34	31	30	25	20				
1.25	75	67	61	55	50	47	70	63	57	52	47	44	49	46	42	40	36	35	29	24				
1.50	80	71	66	60	55	52	74	66	62	56	52	49	53	50	46	44	40	39	32	27				
2.00	88	77	75	67	65	60	81	72	70	64	61	57	61	56	54	51	47	45	39	32				
2.50	93	80	81	72	72	65	86	76	76	68	67	61	65	60	59	55	51	49	43	36				
3.00	97	83	86	76	77	69	89	78	80	71	72	65	69	64	63	59	55	52	46	39				
4.00	102	87	93	80	85	75	94	82	86	76	79	71	74	68	69	64	59	57	50	43				
5.00	105	89	97	83	90	78	97	84	90	79	84	75	78	71	73	67	63	60	54	46				
10.00	112	94	107	91	103	87	104	89	100	86	96	83	86	77	83	75	71	67	61	54				

