

SUNLITE-EC

sunlite

Sunlite Suite USB & Ethernet DMX Controller



Overview

Featuring 1024 DMX channels, the SUNLITE-EC is compatible with Sunlite Suite 2 and 3 running in express mode out of the box. The Ethernet connection allows a range of connectivity options.

As well as live performance, this interface can operate as a Stand Alone DMX controller, for use with RGB/RGBW and more advanced moving and color mixing luminaires.

SUT (Smart Upgrade Technology) enables upgrades such as Artnet universes and compatibility with additional software and apps when purchased at store.dmxsoft.com.

www.sunlitepro.com

Key Features

- 2x DMX512 universes in live mode
- 1x DMX512 universes in stand alone mode
- Expandable to 4 DMX512 universes *
- Intuitive backlit keyboard with 10 presets
- Standalone mode with 99 scenes across 5 zones
- USB & Ethernet for programming/control
- Multi-zone microSD memory
- 16 dry contact trigger ports via HE20 connector
- Clock and calendar triggering (* optional)
- Sunlite Suite 2 & 3 Express Mode (upgradable to Full Mode *)
- Phone/iPad/Android remote and programming apps
- DMX in or out. RDM ready.
- USB-C Protection
- Smart Upgrade Technology (SUT)

* SUT upgrades from store.dmxsoft.com

Technical Data

Input Power	5-5.5V DC 0.6A
Output Protocol	DMX512
Connections	Type C USB, XLR3, Ethernet, HE20, battery
TCP Connections	2
Memory	microSD SD & SDHC (32Gb Max)
Environment	IP20. 0°C - 50°C
Buttons	10 buttons for direct access 2 buttons to change scene + 1 button to change zone
Dimensions	160x90x45mm 268g
OS Requirements	Sunlite 2 & 3 requires Windows 10/11 64bit ESA2 MacOS 10.13.6+
Standards	ETL, EC, EMC, ROHS

Optional Accessories

POWER1_EU/UK/US	5V ACDC power supply with EU/UK/US plug
METAL BRACKET	For mounting against a wall. Supplied on request

CONNECTIVITY

Live use with a computer



Stand Alone or live use with a smartphone/tablet

